

IN THE APPLICATION

OF


Sheila Bokina

FOR

Surgical Tape Dispenser

FILED WITH

THE UNITED STATES PATENT AND TRADEMARK OFFICE

EXPRESS MAIL MAILING CERTIFICATE
Express Mail mailing label number: EE 353 878 155 US
Date of Deposit 19 January 2004
I hereby certify that this paper or fee is being deposited with
the United States Postal Service "Express Mail Post Office to
Addressee" under 37 CFR 1.10 on the date indicated above and is
addressed to "Mail Stop Patent Applications, Commissioner
for Patents, P.O. Box 1450, Alexandria, Virginia 22313-1450"

Michael J. Krolik
Attorney for Applicant

Bokina; Doc. No. SB-1-gw; 3 Dec. 2003

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to tape dispensers and, more specifically, to a tape dispenser having a plurality of spindles that will hold various width tape rolls within a housing containing compartments for the tape rolls. The housing is comprised of a rigid material having a plurality of grooves on opposing walls of the housing for axially mounting spindles holding tape rolls therewith. There are serrated members extending from the housing enabling tape to be sheared into any length needed.

Description of the Prior Art

There are other dispenser devices designed for rolled tape. Typical of these is U.S. Patent No. 2,647,700 issued to Lathrop on August 4, 1953

Another patent was issued to Castelli on August 10, 1965 as U.S. Patent No. 3,199,394. Yet another U.S. Patent No. 3,870,211 was issued to Schriever on March 11, 1975 and still yet another was issued on October 4, 1988 to Tegg U.S. Patent No. 4,775,109.

Another patent was issued to Sigmund on October 10, 1989 as U.S. Patent No. 4,872,601. Yet another U.S. Patent No. 5,160,077 was issued to Sticklin on November 3, 1992. Another was issued to Niada on September 21, 1999 as U.S. Patent No. 5,954,256 and still yet another was issued on May 2, 2000 to Von Schenk as U.S. Patent No. 6,056,233.

Another patent was issued to Paal, et al. on April 2, 2002 as U.S. Patent No. 6,364,245. Yet another U.S. Patent Publication No. 2002/0121537 was issued to Petterson, et al. on September 5, 2002.

U.S. Patent Number 2,647,700

Inventor: Harvey Lathrop

Issued: August 4, 1953

The combination with a dispensing spool of adhesive tape comprising a hub and a tangential projection eccentric to the hub to support the free end of the tape, of a supporting enclosure comprising a pair of parallel vertical walls, means carried by said walls for engaging the spool hub to support the latter in a horizontal disposition and for free rotation about its axis, transverse walls extending between said vertical walls to form an enclosure closed on all sides but one, the open side lying in a single plane so that the enclosure may be rested thereon to conceal said spool, the transverse wall adjacent to said open side being flat so that the enclosure may be optionally rested on said flat wall to bring the open side into upright position and thereby expose and afford access to said spool, said spool being supported with its tangential projection downward and facing away from said flat wall when the enclosure is in the spool concealing position, whereby the eccentricity of said projection automatically causes it to protrude out of said open side of the enclosure when the enclosure is rested on said flat wall.

U.S. Patent Number 3,199,394

Inventor: Charles Castelli

Issued: August 10, 1965

In a tape dispenser a pair of end sections disposed parallel to each other, each end section having a rear portion and a front portion, a cutter guide extending between and secured to the front portions of said end sections, a tape container comprising a body section, a cover and the rear portions of said end sections, a hinge connecting said cover to said body section, a plurality of spacers in said body section for positioning rolls of tape placed in said container, said spacers having slots therein for removably supporting a spindle thereon, means carried by said cover for maintaining said spindle in said slots when said cover is in a closed position, and a cutter movable along said cutter guide for severing sections of tape.

U.S. Patent Number 3,870,211

Inventor: Fred G. Schriever

Issued: March 11, 1975

A multiple tape dispenser comprising, a cylindrical housing having a plurality of reels of tape rotatably mounted in the housing and spaced apart in fixed relationship to each other, said housing having an edge over which the housed tape may be dispensed, and a cutting means affixed to the housing and located near the edge of the body member for cutting a length of desired tape at the point the tape is dispensed.

U.S. Patent Number 4,775,109

Inventor: Duane T. Tegg

Issued: October 4, 1988

A multi-compartmented toilet paper holder includes a mounting plate, which is attachable to a vertical wall. A housing pivotally engages the mounting plate to permit pivoting of the housing between open and closed positions. In one embodiment of the invention, an intermediate wall divides the interior of the housing into upper and lower compartments. In another embodiment of the invention, an intermediate wall divides the housing into side-by-side lateral compartments. Each compartment is of a size to accommodate a roll of toilet paper and each compartment has an access opening through which the paper is dispensed at the lower portion thereof.

U.S. Patent Number 4,872,601

Inventor: Jerry A. Sigmund

Issued: October 10, 1989

A wall mounted toilet tissue dispenser for two very large rolls of toilet tissue. The rolls are rotatably supported side by side in the dispenser with the axis of each roll perpendicular to the mounting wall of the dispenser. Paper is dispensed through a dispensing opening located at the bottom of the dispenser. Tail guide members are provided in the dispenser for limiting the location in the dispensing opening of the tail of each roll of tissue and for guaranteeing that the paper is at an angle to the vertical when the paper is severed so that after the paper is cut the tail will project below the dispensing opening when the paper falls to a vertical position.

U.S. Patent Number 5,160,077

Inventor: Scott J. Sticklin

Issued: November 3, 1992

An apparatus for holding, containing, and dispensing sterile, hygienic cordage, such as dental floss and suture materials is disclosed. The apparatus comprises: a housing; and cutting and retaining means. The housing has a depression formed therein across which the cordage is placed. The apparatus allows a user to grasp the cordage, withdraw a desired length of cordage, and sever a trailing end thereof without manually touching the apparatus. This reduces the threat of cross-contamination between successive uses and/or users of the apparatus.

U.S. Patent Number 5,954,256

Inventor: Gianandrea Niada

Issued: September 21, 1999

A container device that dispenses paper from a roll, with a roll (B) in reserve is disclosed. The device has two substantially parallel pins (4,4') for supporting and unwinding paper from the rolls (A, B) with two openings corresponding to the pins in the lower portion of the device contained within a housing. A sector shaped as part of a circle is mounted to freely rotate about one of the pins. The sector has a peripheral flange that is adapted to obstruct the corresponding opening. When the sector is kept at a first, substantially vertical position, the opening is obstructed. A spring urges the sector to rotate until reaching a second position at which point, the previously obstructed opening is made accessible. A lever is provided to keep the sector in a first position until a thumb follower, attached to the lever comes into contact with the core of the roll upon roll exhaustion, whereby the sector rotates to a second position making the opening accessible.

U.S. Patent Number 6,056,233

Inventor: David R. Von Schenk

Issued: May 2, 2000

A cover system for toilet paper to protect the toilet paper from dispersal by children and pets comprising a wall-mounted plastic casing completely covering upper and lower rolls of paper. The upper and lower rolls are covered by respective upper and lower swivelable covers, each having a safety latch system. Each safety latch system includes a pair of button-releasable latches with one button on each side of the casing and each cover may be released only by pushing both such buttons at the same time. The covers are light permeable and night lights may be mounted to the inside of the casing or as part of each holder going through each toilet paper roll.

U.S. Patent Number 6,364,245

Inventor: Alan P. Paal, et al.

Issued: April 2, 2002

A dispenser for selectively dispensing first and second rolls of sheet material respectively wrapped around first and second cores is provided. The dispenser includes a housing defining a storage compartment for the first and second rolls and an opening, a first and second core support structures disposed in the housing for respectively supporting differently sized first and second cores and a divider slidably carried by the housing and covering a portion of the opening. The divider is movable between a first dispensing position, wherein a first portion of the opening is uncovered to allow access to the first roll and a second portion of the opening is covered to prevent access to the second roll, and a second position, wherein the first portion of the opening is covered and the second portion the opening is uncovered to allow access to the second roll. The divider includes an adjustable blocking plate for preventing movement of the divider from the first dispensing position to the second dispensing portion until substantially all the sheet material has been exhausted from the first roll. The plate is positionable on the divider in a plurality of positions relative to the first core support structure to compensate for different diameter cores.

U.S. Patent Publication No. 2002/0121537

Inventor: Tor Petterson, et al

Issued: September 5, 2002

Dispenser for rolls of a web-shaped material, such as paper, said dispenser having space for at least two rolls arranged substantially horizontally, at which one space is located adjacent the outlet opening and is intended for a first roll in a use position and the second space is located above the first space and is intended for a roll in standby position. A locking means is intended to keep the second roll in standby position. The first space is provided with a vertically arranged disk plate having a flange intended to grip around one end of the roll and keep it in use position. The disk plate is spring-loaded and cooperates with the locking means in such a way that when a roll is located in place in the disk plate the locking means prevents the standby roll from falling down, but when the roll is removed from the disk plate the locking means can be released and permit the standby roll to fall down to use position in the disk plate.

While these dispensers may be suitable for the purposes for which they were designed, they would not be as suitable for the purposes of the present invention, as hereinafter described.

SUMMARY OF THE PRESENT INVENTION

The present invention discloses a tape dispenser having a plurality of spindles that will hold various width tape rolls within a housing containing compartments for the tape rolls. The housing is comprised of a rigid material having a plurality of grooves on opposing walls of the housing for axially mounting spindles holding tape rolls therewith. There are serrated members extending from the housing enabling tape to be sheared into any length needed. The cover also has pivots and a locking element.

A primary object of the present invention is to provide a tape dispenser having a pivoting dust cover and locking mechanism.

Another object of the present invention is to provide a housing that will hold a plurality of tape spindles.

Yet another object of the present invention is to provide a tape dispenser for holding various width tape rolls.

Still yet another object of the present invention is to provide a tape dispenser having apertures for wall mounting.

Another object of the present invention is to provide a tape dispenser having serrated members for efficiently shearing tape.

Yet another object of the present invention is to provide a contamination free environment for surgical tape rolls.

Still yet another object of the present invention is to provide a housing having grooves for grasping tape.

Additional objects of the present invention will appear as the description proceeds.

The present invention overcomes the shortcomings of the prior art by providing a tape dispenser having a plurality of spindles that will hold various width tape rolls within a housing containing compartments for said tape rolls. The housing is comprised of a rigid material having a plurality of grooves on opposing walls of said housing for axially mounting spindles holding tape rolls therewith. There are serrated members extending therefrom said housing enabling tape to be sheared into any length needed.

The foregoing and other objects and advantages will appear from the description to follow. In the description reference is made to the accompanying drawings, which form a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. These embodiments will be described in sufficient detail to enable those skilled in the art to practice the invention, and it is to be understood that other embodiments may be utilized and that structural changes may be made without departing from the scope of the invention. In the accompanying drawings, like reference characters designate the same or similar parts throughout the several views.

The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is best defined by the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the invention may be more fully understood, it will now be described, by way of example, with reference to the accompanying drawings in which:

Figure 1 is an illustrative view of the present invention.

Figure 2 is a perspective view of the present invention.

Figure 3 is a perspective view of the present invention.

Figure 4 is an exploded view of the present invention.

Figure 5 is a side view of the present invention.

Figure 6 is a perspective view of the dust cover of the present invention.

Figure 7 is a side view of the dust cover of the present invention.

Figure 8 is a back perspective view of the present invention.

LIST OF REFERENCE NUMERALS

With regard to reference numerals used, the following numbering is used throughout the drawings.

10	present invention
12	tape dispenser
14	tape roll
16	dust cover
18	wall
20	serrated edge
22	pivot point
24	locking element
26	spindles
28	groove
30	housing
32	spacer
34	finger notch
36	apertures

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The following discussion describes in detail one embodiment of the invention. This discussion should not be construed, however, as limiting the invention to those particular embodiments since practitioners skilled in the art will recognize numerous other embodiments as well. For a definition of the complete scope of the invention, the reader is directed to the appended claims.

Turning to Figure 1, shown therein is an illustrative view of the present invention 10. Shown is a wall 18 mounted surgical tape dispenser 12 providing means for holding multiple rolls of tape 14 and having an anti contamination dust cover 16 for accessing tape or changing tape rolls.

Turning to Figure 2, shown therein is a perspective view of the present invention 10. Shown is the present invention 10 comprised of a housing 28 made of rigid material and having means for supporting a plurality of tape rolls 14 on spindles 26 with multiple serrated members 20 or cutting edges for shearing small or large amounts or pieces of tape from the master roll 14. Also shown are dust cover 16 mounted pivotally at pivot point 20 on one end with a locking element at 22 on the other end.

Turning to Figure 3, shown therein is a perspective view of the present invention 10. Shown is the dust cover 16 pivoted downward leaving access for the removal of the tape spindles 26. The

ends of the spindles 26 rotate within the grooves 28 of the rigid housing 30.

Turning to Figure 4, shown therein is an exploded view of the present invention 10. Shown is the tape dispenser having a rigid multilevel tape roll support member with removable tape spindle 26 cores for holding a plurality of tape rolls 14. The dust cover 16 provides a contamination free environment for any type of tape including surgical tapes. Also shown are pivot 22, locking nub 24 and spaces 32.

Turning to Figure 5, shown therein is a side view of the present invention 10. Shown is the tape dispenser having serrated members 20 extending outward from the dispenser housing 30. The finger notches 34 within the dispenser housing 30 allow clearance for grasping the tape.

Turning to Figure 6, shown therein is a perspective view of the dust cover 16 of the present invention. Shown is the dust cover 16 of the present invention comprising a rigid material having a pivot 22 at the bottom most end with a locking nub 24 located on the upper portion of the cover.

Turning to Figure 7, shown therein is a side view of the dust cover 16 of the present invention. Shown is the dust cover 16 of the present invention comprising a rigid material having a pivot or nub 22 at the bottom end and a locking nub 24 located at the top portion of the device.

Turning to Figure 8, shown therein is a back perspective view of the present invention 10.

Shown are the multiple wall mounting apertures 36 within the housing 30 of the tape dispenser that will allow fasteners to pass therethrough for wall mounting.